

取扱商品在庫表 (単位: kg/枚)

== 縞鋼板 ==

商品名称	規格 / 鋼種	板厚	kg / m ²	914 x 1829	1219 x 2438	1524 x 3048
縞鋼板 (NFP)	一般用	2.3	19.73	33.0	58.6	-
		3.2	26.79	44.8	79.6	124.0
		4.5	36.99	61.8	110.0	172.0
		6.0	48.77	81.5	145.0	227.0
		9.0	72.32	121.0	215.0	336.0
		12.0	95.87	160.0	285.0	445.0
		16.0	127.27	213.0	378.0	591.0
		19.0	150.82	-	448.0	701.0
プレメッキ 縞鋼板	一般用	2.3	19.73	33.0	58.6	-
		3.2	26.79	44.8	79.6	124.0
		4.5	36.99	61.8	110.0	172.0
		6.0	48.77	81.5	145.0	-
カラー 縞鋼板	一般用	3.2	26.79	44.8	79.6	-
		4.5	36.99	61.8	110.0	-

== エキスパンドメタル ==

商品名称	メッシュ (mm)		ストランド (mm)		kg / m ²	914 x 1829	1219 x 2438	1524 x 3048
	SW	LW	T	W				
エキスパンドメタル								
XG-11	34	135.4	4.5	7.0	14.50	24.20	43.10	67.40
XG-12	34	135.4	6.0	7.0	19.40	32.40	57.70	90.10
XG-13	34	135.4	6.0	9.0	24.90	41.60	74.00	116.00
XG-21	36	101.6	4.5	7.0	13.70	22.90	40.70	63.60
XG-22	36	101.6	6.0	7.0	18.30	30.60	54.40	85.00
XG-23	36	101.6	6.0	9.0	23.60	39.50	70.10	110.00
XG-24	36	101.6	8.0	9.0	31.40	52.50	93.30	146.00
XS-31	12	30.5	1.2	1.5	2.36	3.95	7.01	-
XS-32	12	30.5	1.6	2.0	4.19	7.01	12.50	19.50
XS-33	12	30.5	2.3	3.0	9.03	15.10	26.80	41.90
XS-41	22	50.8	1.6	2.0	2.28	3.81	6.78	-
XS-42	22	50.8	2.3	2.5	4.10	6.86	12.20	19.00
XS-43	22	50.8	3.2	3.5	8.00	13.40	23.80	37.20
XS-61	34	76.2	2.3	3.0	3.19	5.33	9.48	-
XS-62	34	76.2	3.2	4.0	5.91	9.88	17.60	27.50
XS-63	34	76.2	4.5	5.0	10.40	17.40	30.90	48.30

注)XS-63につきましては、ソロバン目の他にタタミ目も通常在庫品でございます。

== アンチスリップ鋼板 ==

商品名称	タイプ	開口率	板厚	914 x 1829	1219 x 2438	1524 x 3048
アンチスリップ 鋼板 KST	片面タイプ	約 6%	1.6	20.1	-	-
			2.0	25.1	-	-
			3.2	39.5	70.1	110.0
			4.5	55.6	98.6	154.0
			6.0	74.2	131.0	206.0
アンチスリップ 鋼板 KSR	両面タイプ	約 12%	3.2	37.1	65.6	103.0
			4.5	52.2	92.2	145.0
			6.0	69.6	123.0	193.0

== アンチスリップ鋼板 ==

商品名称	タイプ	開口率	板厚	914 x 1829	1219 x 2438	1524 x 3048
パンチングメタル 60° 千鳥抜	3φ-5p	32.6%	1.0	8.8	15.7	-
			1.2	10.6	18.9	-
			1.6	14.2	25.1	-
	5φ-8p	35.4%	1.2	10.2	18.1	-
			1.6	13.6	24.1	-
			2.3	19.5	34.7	-
	6φ-9p	40.2%	1.2	9.4	16.7	-
			1.6	12.6	22.3	-
			1.2	9.4	16.7	-
	10φ-15p	40.2%	1.6	12.6	22.3	-
			2.3	18.1	32.1	-
			3.2	25.1	44.7	-

